



Recessed Led Linear Grille Downlight

LED Laser Blade Light 20w Model No.:SL-SD35520 Version: V1.0

Date: June 8th,2022





□ 275*35

Features

- Optic Lens Output Oval Distribution , Especially Suitable For Lighting Long And Narrow Spaces, Such As Corridors Or Passage Areas, And Kitchen Island Or Dinning Table .
- Aluminum Housing With Excellent Thermal Dissipation.Sand White Or Sand Black Finish.
- Glareless, Exquisite And Dexterous Design Ensure Highly Integrated In Installation Space.
- Ra90 High Color Rendering Is More Realistic, Restores The True Color Of The Subject.
- Provided 5/10/15 Grille Eyes With Wattage From 10W To 30W.
- Anit Glare Round Or Square Reflector No Dazzling Lighting, Protect Eyes.
- Adjustable Type,Frameless Type And Surface Mounted Type Available For Choose.
- \bullet Supporting To Triac Dimming, 0/1-10V And Dali Dimming Smart Control System .
- 3-5 Years warranty.

Application Scenarios

Widely Used In Commercial Lighting Like Hotels, Villas, Offices, And Residental Lighting, Etc. Sepcially Suitable For Corridors Or Passage Areas.

Luminaire Specification

Height	H 42mm	
Wide	W 45mm	
Length	L 275mm	
Material	Aluminium+PC	
IP Rating	IP20	
Cutout	Ø 275*35mm	

LED Specification

LED	SMD Bridgelux
Output	20W
CRI	Ra90
CCT	2700K, 3000K,4000K,5000K
Lumen	1600lm
Beam angle	15° / 24° / 36°
Drive current	DC600mA,21V~35V
Input voltage	AC220~240V / 50-60Hz
Finish	Sand White / Sand Black

Ordering Information

	Beam angle	LED driver brand	LED CCT	Driver type	Power
1	Narrow 15°	1 Lifud	1 2700K	1 Triac dimming	A 20W
2	Medium 24°	2 Kegu	2 3000K	2 0-10V Dimming	
3	Wide 36°	3 Eaglerise	3 4000K	3 DALI Dimming	
			4 5000K	4 Regular Non-dimming	